



















DURSTONE

PORCELÁNICO

FICHA TÉCNICA PRODUCTO

MODELO
COLOR
ACABADO
FORMATO

FRAME
ALL COLORS
NATURAL
60X60- 8,50mm

		Test Standard UNE-EN ISO 10545	Product Standard ISO 13006-EN1441	DURSTONE VALUES
Características dimensionales <i>Dimensional and Surface Appearance</i>				
	Espesor <i>Thickness</i>	ISO 10545-2	± 0,05%	Cumple/Achieved
	Longitud y anchura <i>Length and width</i>	ISO 10545-2	± 0,05%	Cumple/Achieved
	Ortogonalidad <i>Squareness</i>	ISO 10545-2	± 0,6%	Cumple/Achieved
	Planaridad <i>Surface Flatness</i>	ISO 10545-2	± 0,05%	Cumple/Achieved
Propiedades físicas <i>Physical properties</i>				
	Absorción de agua <i>Water absorption</i>	ISO 10545-3	≤ 0,3%	<0,3%
	Resistencia a flexión N/mm² <i>Modulus of rupture</i>	ISO 10545-4	≥ 35	51
	Carga de ruptura N <i>Breaking strength</i>	ISO 10545-4	≥ 1300	2400
	Resistencia a la abrasión profunda <i>Resistance to deep abrasion</i>	ISO 10545-6	≤ 175	140-135
	Resistencia al choque térmico <i>Resistance to thermal shock</i>	ISO 10545-9	Exigida/Required	Cumple/Achieved
	Resistencia a la helada <i>Frost resistance</i>	ISO 10545-12	Exigida/Required	Cumple/Achieved
	Resistencia al rayado (MOHS) <i>Scratch resistance (MOHS)</i>	UNE EN-101		8
	Deslizamineto <i>Antislip</i>	ENV 12633	-	CLASE 1
		DIN 51130	-	R 9
		ANSI A 137.1	>42	DCOF >42
		BS7976-2	≥36	PTV >36
Propiedades químicas <i>Chemical properties</i>				
	Resistencia a productos de limpieza y aditivos <i>Resistance to household chemical ans swimming pool</i>	ISO 10545-13	Min. GB/UB	UA
	Resistencia a ácidos y bases <i>Resistance to acids and alkalis (low concentration)</i>	ISO 10545-13	GLB/ULB	ULA
	Resistencia a ácidos y bases <i>Resistance to acids and alkalis (high concentration)</i>	ISO 10545-13	GHB/UHB	UHA
	Resistencia a las manchas <i>Resistance to staining</i>	ISO 10545-13	Min. 3	5

CALIDAD Y PRODUCTO
CASA DEPOT, S.L.
DURSTONE CADE, S.L.